## WHAT IS CLAIMED IS:

1. A video signal processing apparatus, comprising:

an amplifier having an input for receiving a chroma input signal, an output for providing a chroma output signal;

a control circuit coupled to the amplifier for controlling the amplitude of a burst component of the output signal characterized in that

the control circuit reduces the amplitude of the output signal in a controlled manner when the value of the burst component is below a predetermined value.

- 2. Apparatus according to Claim 1,
  15 characterized in that the control circuit comprises a
  first feedback path coupled to the amplifier and a
  second feedback path coupled to the first feedback path.
- 3. Apparatus according to Claim 2,
  20 characterized in that the first feedback path comprises
  a filter and the second feedback path is connected in
  parallel with the filter for controlling the values of a
  characteristic knee and/or slope characteristic of the
  apparatus for burst amplitudes below a given knee value.

4. In a television apparatus, an ACC system, comprising:

a controllable amplifier having an input for receiving a chroma input signal, an output for providing an chroma output signal of controllable amplitude, and a gain control input; and

a dircuit for controlling the gain of the controllable amplifier, characterized in that the circuit comprises

first feedback path including a cascade connection of a means for providing a signal representative of a measured burst amplitude, a means for providing an error signal representative of the difference between a desired burst amplitude and the

25

30

35

5

10

118 11 

measured burst amplitude, and an integrator, coupled between the output of the controllable amplifier and a gain control input of the controllable/amplifier, for integrating the error signal, and

a second feedback path coupled from an output of the integrator to an input of the integrator for reducing the gain of the amplifier at a predetermined rate for values of a burst component of the chroma input signal below a predetermined threshold value.

5. The ACC system according to Claim 4, characterized in that the second feedback path includes: circuit means for/scaling, offsetting and limiting the integrator output signal to provide a control signal; and

means for applying the control signal to the input of the integrator/.

- The ACC system according to Claim 4, characterized in that the means for providing a signal representative of a/measured burst amplitude comprises a burst gate.
- The ACC system according to Claim 4, characterized in that the means for providing a signal 25 representative/of a measured burst amplitude comprises a add Al comel. chroma demodu /ator and a burst accumulator.

10 15

5

20